

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

Art. No.: 70064068

GTIN: 4026397673524



List price: 196.35 €

incl. 19% VAT.

Features:

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED - not for conventional light bulbs
- 16 integrated show programs
- Control via RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Logistic

EAN / GTIN: 4026397673524  
Weight: 2,85 kg  
Length: 0.34 m  
Width: 0.31 m  
Height: 0.12 m

Package contents

- 1 x device, 1 x user manual, 1 x power cord

Technical specifications:

|               |                 |
|---------------|-----------------|
| Power supply: | 230 V AC, 50 Hz |
| Output power: | Max. 200 W      |
|               | Max. 800 W      |

|                                |   |
|--------------------------------|---|
| Power connection:              | Mains input via P-Con (blue), mounting version power supply cord with safety plug   |
| Power output:                  | 4 x safety contact (F), hinged lid mounting version fused<br>1 x P-Con (gray), mounting version Bypass  |
| Device fuse:                   | 5 x 20 mm, F 6 A fuse replaceable   |
| Power output fuse per channel: | 5 x 20 mm, T 1 A fuse replaceable   |
| DMX channels:                  | 1; 4; 6   |
| DMX input:                     | 3-pin XLR (M)   |
| DMX output:                    | 3-pin XLR (F)   |
| Control:                       | RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Control channels:              | 4   |
| Flying points:                 | 2 x M10 thread  |
| Display type:                  | LCD display   |
| Status LED:                    | Chanal level meter  |
| Color:                         | Black   |
| Dimensions:                    | Width: 21 cm<br>Depth: 29 cm<br>Height: 9 cm  |
| Weight:                        | 2,53 kg   |
| Noise classification:          | Class 0 (no noise at all)   |