

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

Art. No.: 70064068

GTIN: 4026397673524



Features:

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED - not for conventional light bulbs
- 16 integrated show programs
- Control via RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Logistic

EAN / GTIN: 4026397673524

Weight: 2,85 kg

Length: 0.34 m

Width: 0.31 m

Height: 0.12 m

Technical specifications:

|                   |                                                                                   |
|-------------------|-----------------------------------------------------------------------------------|
| Power supply:     | 230 V AC, 50 Hz                                                                   |
| Output power:     | Max. 200 W<br>Max. 800 W                                                          |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |

|                                |                                                                                                                                                                         |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power output:                  | 4 x safety contact (F), hinged lid mounting version fused<br>1 x P-Con (gray), mounting version Bypass                                                                  |
| Device fuse:                   | 5 x 20 mm, F 6 A fuse replaceable                                                                                                                                       |
| Power output fuse per channel: | 5 x 20 mm, T 1 A fuse replaceable                                                                                                                                       |
| DMX channels:                  | 1; 4; 6                                                                                                                                                                 |
| DMX input:                     | 3-pin XLR (M)                                                                                                                                                           |
| DMX output:                    | 3-pin XLR (F)                                                                                                                                                           |
| Control:                       | RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Control channels:              | 4                                                                                                                                                                       |
| Flying points:                 | 2 x M10 thread                                                                                                                                                          |
| Display type:                  | LCD display                                                                                                                                                             |
| Status LED:                    | Channel level meter                                                                                                                                                     |
| Color:                         | Black                                                                                                                                                                   |
| Dimensions:                    | Width: 21 cm<br>Depth: 29 cm<br>Height: 9 cm                                                                                                                            |
| Weight:                        | 2.53 kg                                                                                                                                                                 |
| Noise classification:          | Class 0 (no noise at all)                                                                                                                                               |

## Scope of delivery:

1 x device  
1 x user manual  
1 x power cord