

EUROLITE DPX-1210 DMX dimmer pack

PRO digital 12-channel modular dimmer pack

Art. No.: 70064140

GTIN: 4026397185645



The article is no longer in our assortment.

Features:

- 12-channel dimmer pack with up to 10 A output per channel
- Modular design of the individual dimmer modules, the control module, and the connection module for quick and easy change
- 3-phase or 1-phase power supply
- DMX512 control or analog control
- Synchronization of several DPX-1210 possible via DMX
- Adjustable lamp preheat (0-50%) to prolong bulb life assignable to each channel
- Dimmer curves (linear, square, switch) assignable to each channel
- DMX fail function: automatic digital input check to detect DMX signal errors
- 12 built-in programs with adjustable speed
- Manual mode for dimming capability without an external lighting controller
- LCD
- Automatic circuit breaker per channel (type C)
- Channel outputs on the rear panel pole connectors
- 16-pin industrial sockets connection option (not included)
- Rack installation
- Only for professional use
- Control via stand-alone; DMX

Logistic

EAN / GTIN: 4026397185645

Weight: 28,85 kg

Length: 0.60 m

Width: 0.59 m

Height: 0.33 m

Technical specifications:

| | |
|---------------|-----------------------------|
| Output power: | Max. 2300 W Max. 27600 W |
| DMX channels: | 12 |

| | |
|-----------------------------|---|
| Control: | Stand-alone; DMX |
| Control channels: | 12 |
| Color: | Black |
| Dimensions: | Width: 48,3 cm Depth: 48,5 cm Height: 17,8 cm |
| Weight: | 25,90 kg |
| Power supply: | 230-380 V AC, 50 Hz |
| Max. power output: | 27600 W |
| Max. current: | 120 A |
| Number of control channels: | 12 |
| Max. output/channel: | 2300 W |
| Max. current/channel: | 10 A |
| Integrated programs: | 12 |
| DMX output: | 3-pin female XLR socket |
| DMX input: | 3-pin male XLR socket |
| Analog input: | 15-pin Sub-D socket, 12 channels, 0-10 V DC |
| Power input: | Terminal block/PG cable screw |
| Fuse: | 12 x C 10 A, 230 V |
| Dimensions (W x D x H): | 482 x 485 x 176 mm |
| | Rack installation with 4 U |
| Minimum mounting depth: | 500 mm |