



The article is no longer in our assortment.

Features:

- 4 controllable channels
- 5 A resistive load per channel
- Maximum current 16 A
- Outputs via 4 safety sockets
- LED display of all channels
- DMX512 input and output
- DMX starting address adjustable via DIP switches
- For truss installation

Logistic

EAN / GTIN: 4026397257205  
Weight: 3,40 kg  
Length: 0.38 m  
Width: 0.26 m  
Height: 0.16 m

Technical specifications:

|                         |   |
|-------------------------|---|
| Power supply:           | 230 V AC, 50 Hz                                 |
| Dimensions:             | Width: 16,5 cm<br>Depth: 11 cm<br>Height: 32 cm |
| Max. power output:      | 3680 W  |
| Max. total current:     | 16 A  |
| Number of channels:     | 4   |
| Resistive load/channel: | 1150 W  |
| Max. current/channel:   | 5 A   |
| Output sockets:         | 4 safety power outlets                          |

|                   |                         |
|-------------------|-------------------------|
| DMX output:       | 3-pin XLR mounting plug |
| DMX input:        | 3-pin XLR mounting jack |
| Analogue control: | 8-pin DIN-socket        |
| Dimensions:       | 320 x 165 x 110 mm      |
| Weight:           | 3 kg                    |