EUROLITE DMX Move Bigfoot Foot Controller 192

A full-fledged DMX light controller in a foot bar, with FX generator

Art. No.: 70064517

GTIN: 4026397592184

List price: 296.31 €

incl. 19% VAT.

Features:

- Fully programmable DMX foot controller for DMX light effect units such as moving heads, scanners and LED spot lights with RGBW color mixture
- 192 DMX channels can be assigned and inverted as desired to 16 control channels (softpatch)
- For 12 fixtures with max. 16 control channels each
- USB port for storing program data
- Quick programming thanks to the integrated FX generator with movement patterns and color effects
- Several effects can be used simultaneously
- Programs can be freely named
- Simply preselect the desired program and trigger it with GO
- Sound control via audio signal or TAP button
- Convenient control of dimmer, fade time and other functions by foot
- 8 encoders on 2 levels for adjusting DMX values
- Blackout function
- Rugged metal housing
- Programmable 15 scenes/chases each with 100 cues)
- Can transmit up to 192 DMX channels
- Control via DMX; Sound to light via Microphone; Sound to light via RCA (F) mounting version
- Monochrome LCD display
- Non-slip pedal housing
- For application areas such as: Stage; mobile djs / entertainer; product presentations and lectures
- Silent operation
- Firmware can be updated

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

Logistic

EAN / GTIN: 4026397592184

Weight: 5,20 kg

Length: 0.49 m

Width: 0.28 m

Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 9 V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via 2-pin screw plug connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 15 scenes/chases each with 100 cues)
DMX channels:	Output 192
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone; Sound to light via RCA (F) mounting version
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices (FAT 32)
USB port:	Typ A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	Non-slip pedal housing
Dimensions:	Width: 45 cm Depth: 24 cm Height: 10 cm
Weight:	4,72 kg
Noise classification:	Class 0 (no noise at all)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.