

FUTURELIGHT DMX Split 6 Splitter CRMX

6-fold splitter and wireless DMX receiver (2.4 GHz) for truss and wall mounting

Art. No.: 70064822

GTIN: 4026397726329



Features:

- DMX splitter for splitting one DMX input signal to 6 DMX outputs
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Input and outputs galvanically isolated
- Can transmit up to 512 DMX channels
- Each DMX output with active signal processing
- Control via DMX; CRMX by LumenRadio; W-DMX by wireless solution
- Operating range up to 500m with line-of-sight
- 2.4 GHz license-free worldwide
- Up to 10 transmitters can be operated in parallel without interference
- Ultra-low latency
- With Holder for wall mounting

Logistic

EAN / GTIN: 4026397726329  
Weight: 1,60 kg  
Length: 0.23 m  
Width: 0.18 m  
Heigh: 0.13 m

Technical specifications:

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                                                              |
| Power consumption: | 10 W                                                                                |
| IP classification: | IP20                                                                                |
| Protection class:  | Protection class I                                                                  |
| Power connection:  | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug |
| Fuse:              | 5 x 20 mm, F 1 A fuse replaceable                                                   |
| DMX channels:      | Output 512                                                                          |

|                    |                                                                                                                        |
|--------------------|------------------------------------------------------------------------------------------------------------------------|
| DMX input:         | 3-pin XLR (M) mounting version                                                                                         |
| DMX output:        | 3-pin XLR (F) mounting version<br>6 x 3-pin XLR (F) mounting version separate (galvanic) with active signal processing |
| Control:           | DMX; CRMX by LumenRadio; W-DMX by wireless solution                                                                    |
| Range:             | Range up to 500m with line-of-sight                                                                                    |
| Frequency band:    | 2.4 GHz                                                                                                                |
| Parallel mode:     | Max. 10 transmitter                                                                                                    |
| Antenna gain:      | 5 dBi                                                                                                                  |
| Latency:           | < 5 ms                                                                                                                 |
| Modulation:        | GFSK                                                                                                                   |
| Housing color:     | Black                                                                                                                  |
| Attachment system: | M10 thread<br>Holder for wall mounting                                                                                 |
| Status LED:        | DMX, pairing, power, level meter                                                                                       |
| Dimensions:        | Length: 13.7 cm<br>Width: 12.2 cm<br>Height: 11.2 cm                                                                   |
| Weight:            | 1.20 kg                                                                                                                |

**Scope of delivery:**

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x antenna
- 1 x mounting bracket
- 2 x strap
- 1 x declaration of conformity