

EUROLITE DMX Split 8X RDM Splitter

Splitter (RDM) with 8 galvanically isolated outputs, 3/5-pin & QuickDMX XLR sockets

Art. No.: 70064826

GTIN: 4026397554182



Features:

- DMX splitter for splitting one DMX input signal to 8 DMX outputs
- Switchable filter mode allows all RDM data to be filtered out in order to prevent problems when using fixtures intolerant of RDM
- Input and outputs XLR 3-pin and 5-pin each
- Input and outputs galvanically isolated
- Input and outputs with a set of respective power supply and internal fuse
- Switchable termination resistor
- (19") 48.3 cm rack installation 1 U
- Each DMX output with independent driver and status indicator
- Control via QuickDMX via 5-pin XLR (M) mounting version (optional); RDM

Logistic

EAN / GTIN: 4026397554182
Weight: 3,00 kg
Length: 0.54 m
Width: 0.22 m
Heigth: 0.12 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	5 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	8 x 3-pin XLR (F) mounting version separate (galvanic) with independent driver and status indicator

	8 x 5-pin XLR (F) mounting version separate (galvanic) with independent driver and status indicator
	1 x 5-pin XLR (F) mounting version Bypass
	1 x 3-pin XLR (F) mounting version Bypass
Control:	QuickDMX via 5-pin XLR (M) mounting version (optional); RDM
Control elements:	Bypass/terminating resistor switch, power switch
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48.3 cm Depth: 14.5 cm Height: 4.45 cm
Weight:	2.65 kg

Scope of delivery:

1 x device
1 x user manual
1 x power cord