

## MADRIX LUNA 16 Port USB / Art-Net Node

Art-Net and USB interface for output of 8162 channels







# List price: on demand €

incl. 19% VAT.

#### Features:

- Can receive and process up to 512 DMX channels
- Can transmit up to 8162 DMX channels
- The device is cooled by passive convection cooling
- Control via Art-Net
- Built with NEUTRIK connector
- The device can be connected via USB to the PC
- (19") 48.3 cm rack installation 2 U
- Made in Germany
- The device can be connected via RJ-45 etherCON (F) mounting version to the PC
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **Technical specifications:**

Power consumption:	5,00 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
DMX channels:	Input 512 Output 8162
DMX input:	1 x 5-pin XLR (M) mounting version

### Logistic

EAN / GTIN: 4026397521467 Weight: 2,75 kg Length: 0.55 m Width: 0.17 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

DMX output:	16 x 5-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 1x RJ-45 etherCON (F) mounting version
Cooling:	Passive convection cooling
Control:	Art-Net
USB port:	USB 2.0, type B
Use of brands:	Built with NEUTRIK connector
PC connect:	Via USB Via RJ-45 etherCON (F) mounting version
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 7,6 cm Height: 8,9 cm
Weight:	2,27 kg