# eurolite®

## EUROLITE DXT-SP 1in/4out PRO DMX RDM Splitter

RDM-capable DMX splitter, 1in/4out with signal boost

Art. No.: 70064867 GTIN: 4026397572469





## List price: 296.31 €

incl. 19% VAT.

#### Features:

- DMX splitter for splitting one DMX input signal to 4 DMX outputs
- Input and feed-through output are duplicated on the front and rear panel and connected in parallel
- Switchable filter mode allows all RDM data to be filtered out in order to prevent problems when using fixtures intolerant of RDM
- Bypass function to process signals from older devices similar to DMX signals
- Output frequency adjustable: 22/44 Hz
- Switchable termination resistor
- Each DMX output with active signal processing
- Outputs galvanically isolated
- Each DMX output can be connected to 32 DMX devices
- Control via RDM
- DMX feed-through for up to 32 further DMX devices<BR>RDM For bidirectional communication over the DMX line<BR>RDM switchable to prevent problems when using fixtures without RDM
- Built with NEUTRIK connector
- Made in Germany
- DMX fail mode (hold; blackout; zero values)
- Package contents
- 1 x device, 1 x external mains adapter, 4 x foot, 1 x user manual

### **Technical specifications:**

Power supply:

100-240 V AC, 50/60 Hz 12V DC 1000 mA

#### Logistic

EAN / GTIN: 4026397572469 Weight: 1,40 kg Length: 0.33 m Width: 0.24 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	3,6 W
Power connection:	Mains input via 4-pin screw plug connector (M) mounting version power supply cord with AC adapter (provided)
DMX input:	2 x 3-pin XLR (M) mounting version
DMX output:	4 x 3-pin XLR (F) mounting version separate (galvanic) with active signal processing
	2 x 3-pin XLR (F) mounting version Bypass
Control:	RDM
DMX features:	DMX feed-through for up to 32 further DMX devices
	RDM For bidirectional communication over the DMX line
	RDM switchable to prevent problems when using fixtures without RDM
DMX fail mode:	Hold; blackout; zero values
Use of brands:	Built with NEUTRIK connector
Dimensions:	Width: 27,5 cm
	Depth: 10 cm
	Height: 4,1 cm
Weight:	1,21 kg