

EUROLITE AF-180 Stage Fan DMX

High-performance DMX wind machine with adjustable air discharge angle

Art. No.: 80208075

GTIN: 4026397719154



Features:

- Great effect when used e.g. with fog, snow and bubble machines
- Output volume adjustable
- Air discharge angle adjustable
- Quick truss installation via QUICK-LOCK Omega bracket
- Rugged metal housing
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Monochrome LCD display
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; video and photography
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397719154

Weight: 13,50 kg

Length: 0.52 m

Width: 0.44 m

Height: 0.43 m

Technical specifications:

| | |
|--------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 180 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | 1 x P-Con (gray), mounting version |

| | |
|-----------------------|---|
| Speed: | 880 RPM - 2650 RPM |
| Maximum airflow: | 3300 m³/h |
| DMX channels: | 1 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Control: | Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Housing color: | Black |
| Display type: | Monochrome LCD display |
| USB port: | Type A |
| Carrying handle: | 1 pc/pcs |
| Dimensions: | Length: 44 cm Width: 25 cm Height: 48.5 cm |
| Weight: | 11.65 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |

Scope of delivery:

1 x device
1 x user manual
1 x power cord
2 x omega bracket