

EUROLITE ESN 7x80 USB LAN LED Moving Message

Art. No.: 80500107

RG moving message display (7x80 pixels) with network connectivity, PC software and IR remote control GTIN: 4026397681314



List price: 296.31 €

incl. 19% VAT.

Features:

- For all kinds of announcements in shops, shop windows, discotheques, bars, pubs, restaurants and reception areas
- Fully programmable via supplied IR remote control or with PC software via USB port and RJ45 network port
- Dot matrix with 560 super bright SMD LEDs
- Large database with various display effects, symbols and graphics
- 99 editable memory locations
- 8 editable bitmap memory locations, 7 font sizes, 16 color combinations, 8 display speeds, 24 display effects, 30 integrated symbols
- 8 animated messages (Welcome, Merry X'Mas, Happy New Year, etc.)
- Programming of sequences
- Timer function
- 2 swivel mounting brackets
- Incl. mounting brackets, power adapter, remote control, PC software, USB and LAN cable
- LED: 560 x SMD R/G
- The device is cooled by passive convection
- Controlling by IR remote control (provided); network cable (provided); via USB (provided)
- The device can be connected via USB to the PC in connection with LED Single-line; The device can be connected via RJ-45 (F) mounting version to the PC in connection with LED Single-line

Logistic

EAN / GTIN: 4026397681314
 Weight: 1,59 kg
 Length: 0.84 m
 Width: 0.08 m
 Height: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz
 5 V DC 3 A

Power consumption:	12 W
IP classification:	IP20
Protection class:	Class III
Power connection:	Mains input via Coaxial power connector (M) power supply cord with AC adapter (provided)
Cable length:	1,8 m
Battery:	2 x 1.5V AAA Micro LR03 alkaline manganese (not included)
LED:	560 x SMD R/G
Network connection:	Protocol: Ethernet TCP/IP via 1x RJ-45 (F) mounting version
Cooling:	Passive convection
Control:	IR remote control (provided); network cable (provided); via USB (provided)
Screen:	Max. 7x80 px
Presentation:	1-line, 13 visible characters 16 colors
Text:	7 fonts
Housing color:	Black
USB port:	USB 2.0, Typ micro USB (F) mounting version
PC connect:	LED Single-line via USB LED Single-line via RJ-45 (F) mounting version
Display:	60 cm x 5,5 cm
Dimensions:	Width: 64,7 cm Depth: 9,7 cm Height: 3,5 cm
Weight:	1,25 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting