eurolite®

# EUROLITE ESN 7x80 USB LAN LED Moving Message

**Art. No.: 80500107**

RG moving message display (7x80 pixels) with network connectivity, PC software and IR remote control

GTIN: 4026397681314

## List price: 296.31 €

incl. 19% VAT.

## Features:

- Fully programmable via supplied IR remote control or with PC software via USB port and RJ45 network port
- Dot matrix with 560 super bright SMD LEDs
- Large database with various display effects, symbols and graphics
- 99 editable memory locations
- 8 editable bitmap memory locations, 7 font sizes, 16 color combinations, 8 display speeds, 24 display effects, 30 integrated symbols
- 8 animated messages (Welcome, Merry X'Mas, Happy New Year etc.)
- Programming of sequences
- Timer function
- 560 powerful LEDs SMD 3535 R/G
- The device is cooled by passive convection cooling
- Control via IR remote control; network cable; via USB; wired remote control
- With Mounting bracket
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting; Wedding/gala/events; Clubs/dancing school; restaurants, bars and hotels

**Package contents**

- 1 x device, 1 x external mains adapter, 1 x uSB stick, 1 x remote control, 1 x uSB cable, 1 x network cable, 2 x angle

## Logistic

EAN / GTIN: 4026397681314

Weight: 1,59 kg

Length: 0.84 m

Width: 0.08 m

Heigth: 0.17 m

## Technical specifications:

| | |
|---|---|
| Power supply: | 5 V DC |
| Power consumption: | 12 W |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter included |
| LED: | 560 x SMD 3535 R/G |
| Network connection: | Protocol: Ethernet TCP/IP via 1x RJ-45 (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; network cable; via USB; wired remote control |
| Image: | Max. 7x80 px |
| Presentation: | 1-line, 13 visible characters<br>16 colors |
| Text: | 7 fonts |
| Housing color: | Black |
| Attachment system: | 2x Mounting bracket |
| USB port: | USB 2.0, Typ micro USB (F) mounting version |
| Display: | 60,5 cm x  5,5 cm |
| Dimensions: | Width: 64,7 cm<br>Depth: 9,7 cm<br>Height: 3,5 cm |
| Weight: | 1,25 kg |
| USB cable | |
| Cable length: | Approx. 1,5 m |
| Plug A: | 1 x USB, type A |
| Plug B: | 1 x micro USB (M) |
| Color: | Black |
| Network cable | |
| Cable length: | Approx. 1,5 m |
| Connector type: | RJ-45 (M) |
| Color: | Black |
| External mains adapter | |
| Power supply: | 100-240 V AC, 50/60 Hz |
| Pin configuration: | Inside + / outside - |
| IP classification: | IP20 |
| Protection class: | Protection class II |
| Cable length: | Approx. 1,5 m |
| Output: | 5 V DC; 3 A; 15 W |
| Color: | Black |
| Remote control | |
| Battery: | 2 x Micro (AAA)  included |
| Angle | |
| Diameter mounting holes: | 1 x Ø8mm; 1 x Ø6mm |
| Material: | Metal, 1,4 mm |
| Color: | Black |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.