

EUROLITE ESN 7x80 USB LAN LED Moving Message

Art. No.: 80500107

RG moving message display (7x80 pixels) with network connectivity, PC software and IR remote control

GTIN: 4026397681314



Features:

- Fully programmable via supplied IR remote control or with PC software via USB port and RJ45 network port
- Dot matrix with 560 super bright SMD LEDs
- Large database with various display effects, symbols and graphics
- 99 editable memory locations
- 8 editable bitmap memory locations, 7 font sizes, 16 color combinations, 8 display speeds, 24 display effects, 30 integrated symbols
- 8 animated messages (Welcome, Merry X'Mas, Happy New Year etc.)
- Programming of sequences
- Timer function
- 560 LEDs SMD 3535 R/G
- The device is cooled by passive convection cooling
- Control via IR remote control; network cable; via USB; wired remote control
- With mounting bracket
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting; wedding/gala/events; clubs/dancing school; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397681314
Weight: 1,59 kg
Length: 0.84 m
Width: 0.08 m
Heigh: 0.17 m

Technical specifications:

Power supply:	5V DC
Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class III

Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter included
Battery:	1.5 V AAA Micro LR03 alkaline manganese included
Lamp type:	LED lamp
LED type:	560 x SMD 3535 R/G
Network connection:	Protocol: Ethernet TCP/IP via 1x RJ-45 (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; network cable; via USB; wired remote control
Image:	Max. 7x80 px
Presentation:	1-line, 13 visible characters 16 colors
Text:	7 fonts
Housing color:	Black
Attachment system:	2x mounting bracket
USB port:	USB 2.0, type micro USB (F) mounting version
Display:	60.5 cm x 5.5 cm
Dimensions:	Width: 64.7 cm Depth: 9.7 cm Height: 3.5 cm
Weight:	1.25 kg
Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
IP classification:	IP20
Protection class:	Protection class II
Cable length:	Approx. 1.5 m
Output:	5 V DC; 3 A; 15 W
Color:	Black
Battery:	2 x Micro (AAA) included
Cable length:	Approx. 1.5 m
Plug A:	1 x USB, type A
Plug B:	1 x micro USB (M)
Color:	Black
Cable length:	Approx. 1.5 m
Connector type:	RJ-45 (M)
Color:	Black
Diameter mounting holes:	1 x Ø8mm; 1 x Ø6mm
Material:	Metal, 1.4 mm
Color:	Black, matte

Scope of delivery:

- 1 x device
- 1 x external mains adapter
- 1 x USB stick
- 1 x remote control

1 x USB cable
1 x network cable
2 x angle
2 x battery