eurolite®

EUROLITE PCI sending card and software

Network control system LED Studio for LED displays

Art. No.: 80503130 GTIN: 4026397673203



The article is no longer in our assortment.

Features:

- Network control system consisting of PCI sending card and media software LED Studio for controlling LED displays with a computer
- 2 x 2-gigabit ethernet outputs, USB port, DVI port
- LED Pixel Mesh: operation with interface (scanning box) 80503120
- Supported formats: 640 x 480 / 800 x 600 / 1024 x 768 pixels
- The device can be connected via RJ-45 (F) mounting version to the PC
- For application areas such as: Advertisement/Shop window; installation; stage
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x device, 1 x USB cable, 1 x adapter cable

Technical specifications:

Power supply:	5V DC 2000 mA
IP classification:	IP20
Connections:	Signal via 1 x USB B (F) mounting version
	Signal via 2 x RJ-45 (F) mounting version
	Signal via 1 x DVI
PC connect:	Via RJ-45 (F) mounting version
Dimensions:	Width: 16 cm
	Depth: 13 cm
	Height: 4,8 cm



Logistic

EAN / GTIN: 4026397673203 Weight: 0,34 kg Length: 0.24 m Width: 0.15 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. 0,24 kg