# eurolite®

### **EUROLITE PSS-1/150 Pixel String**

Flexible LED pixel string









## The article is no longer in our assortment.

#### Features:

- Flexible pixel string with 40 ultra-bright TCL LEDs
- Bright and colorful projection of videos and graphics
- Can be arranged into virtually any form even on uncommon surfaces for creative freedom
- Modular concept allows build-up of large video displays for clubs, stages, shops and various other environments also for billboards on buildings
- Can be extended up to 40 meters with 340 pixels
- IP65 for indoor and outdoor use
- Pixels individually controllable
- Independent control of color, effects and animations
- Control per network protocol with PC software or PSS media player (accessories)
- Control also possible per MADRIX, DMX and Artnet
- Large operating range from -20° to +50° C
- 40 powerful LEDs SMD 3in1 TCL RGB (homogenous color mix)

#### **Technical specifications:**

Power consumption:	0,3 W
IP classification:	IP65
LED:	40 x SMD 3in1 TCL RGB (homogenous color mix)
Dimensions:	Width: 2,3 cm
	Depth: 1,2 cm
	Height: 3 cm

#### Logistic

EAN / GTIN: 4026397423471 Weight: 0,67 kg Length: 0.30 m Width: 0.20 m Heigth: 0.08 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	660 g
Pixel pitch:	75 mm
Pixel configuration:	1 RGB LED (TCL)
Pixels per string:	40
Pixel size (W x D x H):	23 x 30 x 12 mm
String length:	6 m
Max. string length:	40 m
Total max. pixels:	340
Brightness:	2.5 cd per pixel
Bit depth per color:	16
Bit depth per pixel:	48
Viewing angle:	120° x 120°
Lifetime:	approx. 80000 hours
Control protocol:	TCP/IP
Control system:	PSS-1
Display mode:	synchronous to video source
Protection grade:	IP65
Material:	clear polycarbonate
	black cable
Operating temperature:	-20 to 50 °C
Power supply:	5 V DC via control system PSS-1
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting