
eurolite®

EUROLITE GD-25 LED panel 200x400mm

LED display for video and pixel mapping applications











The article is no longer in our assortment.

Features:

- Modular LED display for video and pixel mapping applications
- Bright and colorful projection of videos, animations and graphics
- 25 mm pixel pitch
- 128 pixels (8 x 16)
- RGB SMD 5050 LEDs
- Transparent design
- Modular display concept allows the build-up of large areas
- Ideal for stage/fair construction and fixed installation
- Control via optional AIO processor and PC software
- 128 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)

Technical specifications:

Power supply:	24V DC
Power consumption:	2,7 W
LED type:	128 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Image:	Max. 8x16 px
	Pixel pitch 25 mm
	Pixeldensity 1600/m ²
	Brightness 1600cd/m ²
Dimensions:	Width: 400 cm

Logistic

EAN / GTIN: 4026397561500 Weight: 0,50 kg Length: 0.40 m Width: 0.20 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Height: 200 cm
Weight:	0,25 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting