# eurolite®

### **EUROLITE DF Control system**

Control unit for DF-40 LED display









## The article is no longer in our assortment.

#### Features:

- Control unit and PC software for controlling DF-40 LED displays
- Operation with the handy media player (80503610) or a network-compatible computer
- Create stunning light shows for your displays with the included light effect software
- Load your shows onto the included SD memory card for playback on the media player
- Ethernet input and output, LAN cable included

#### Logistic

EAN / GTIN: 4026397423778 Weight: 1,20 kg Length: 0.20 m Width: 0.17 m Heigth: 0.07 m

#### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10,00 W
Dimensions:	Width: 16 cm
	Depth: 15,5 cm
	Height: 5 cm
Weight:	1,10 kg
Signal input:	RJ45, CAT5e
Signal link:	RJ45, CAT5e
Number of displays:	max. 6 per control unit
Serial connection:	max. 255 control units for PC operation
	max. 48 control units for media player operation
Pixels:	max. 3072

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

160 x 155 x 50 mm
Windows XP, Vista or 7
Separate network card (100 Mbps)
SD card reader