

OMNITRONIC MP-350P PA Mixing Amplifier

PA mixing amplifier with audio player,IR remote control, 350 W RMS

Art. No.: 80709645











List price: 605.71 €

incl. 19% VAT.

Features:

- SD card slot and USB port
- Folder navigation and repeat functions (1, All)
- 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
- Microphone input 3 with adjustable priority circuit
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms audio player
- Control via IR remote control
- LCD display

Package contents

- 1 x remote control, 1 x amplifier, 1 x user manual, 1 x battery

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	700,00 W

Logistic

EAN / GTIN: 4026397504019

Weight: 14,15 kg Length: 0.54 m Width: 0.49 m Heigth: 0.18 m

Power connection: Fixed power supply cord with safety plug Frequency range: 80 - 14000 Hz S/N ratio: >75 dB microphone >85 dB line THD: <0,5 % at 1 kHz Cooling: Temperature-controlled fan , air flow from front to rear Impedance: 4-16 ohms; public address systems 100V; Public address systems 70V Circuitry: Class AB Controls: Power on/off transient; Overvoltage; short-circuit Status LED: Power, fault, master level meter Connections: Input: microphone via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo NCA 0,3 v Output: speaker via screw terminal Channels: Microphon chanal: 2 x mono via jack, channel control via rotary dial, mute control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial, rutte control Waster output: mono, channel control via rotary dial, 2-band one control EQ Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999 Available storage media: USB devices/SD cards max. 32GB (FAT 32)	Output power:	350 W RMS
S/N ratio: >75 dB microphone >85 dB line THD: <pre> <pre></pre></pre>	Power connection:	Fixed power supply cord with safety plug
Set dB line THD:	Frequency range:	80 - 14000 Hz
Cooling: Temperature-controlled fan , air flow from front to rear Impedance: 4-16 ohms; public address systems 100V; Public address systems 70V Circuitry: Class AB Controls: Power on/off transient; Overvoltage; short-circuit Status LED: Power, fault, master level meter Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: line via 3 x stereo RCA 0,3 V Output: rec. via 1 x stereo RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, input chanel: via audio player, channel control via rotary dial, input control input chanel: via audio player, channel control via rotary dial, input control Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	S/N ratio:	'
Impedance: 4-16 ohms; public address systems 100V; Public address systems 70V Circuitry: Class AB Controls: Power on/off transient; Overvoltage; short-circuit Power, fault, master level meter Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: mierophone via 3 x stereo RCA 0,3 V Output: rec. via 1 x stereo RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial, Input chanel: 3 x stereo via RCA, channel control via rotary dial, Input chanel: 3 x stereo via RCA, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	THD:	<0,5 % at 1 kHz
address systems 70V Circuitry: Class AB Controls: Power on/off transient; Overvoltage; short-circuit Status LED: Power, fault, master level meter Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: line via 3 x stereo RCA 0,3 V Output: rec. via 1 x stereo RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, anute control Master output: mono, channel control via rotary dial, anute control Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Cooling:	•
Controls: Power on/off transient; Overvoltage; short-circuit Status LED: Power, fault, master level meter Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x steree RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Input chanel: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x steree via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Impedance:	· · · · · · · · · · · · · · · · · · ·
Status LED: Power, fault, master level meter Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: inc via 3 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Output: peaker via 5 x stereo RCA 0,3 v Outp	Circuitry:	Class AB
Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sereo RCA 0,3 v Output: peaker via 5 x sereo via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sereo RCA 0,3 v Output: peaker via 5 x sereo via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sereo RCA 0,3 v Output: peaker via 5 x sereo via 1 x sono via 2 x 6.3 mm plug (unbal.) Input: inc via 1 x sereo via 1 x sono via 2 x mono via 2 x mo	Controls:	Power on/off transient; Overvoltage; short-circuit
(F) combination socket (mounting version) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Input: microphone via 2 x 5.3 mm plug (unbal.) Output: rec. via 1 x stereo RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Status LED:	Power, fault, master level meter
Input: line via 3 x stereo RCA 0,3 V Output: rec. via 1 x stereo RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19°) 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: R remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Connections:	
Output: rec. via 1 x stereo RCA 0,3 V Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial, Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		
Output: speaker via screw terminal Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		•
socket (XLR/jack), channel control via rotary dial Microphon chanal: 2 x mono via jack, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		•
control via rotary dial Input chanel: 3 x stereo via RCA, channel control via rotary dial Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Channels:	
via rotary dial Input chanel: via audio player, channel control via rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		
rotary dial, mute control Master output: mono, channel control via rotary dial, 2-band tone control EQ Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		·
Material: Metal Color: Black Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Metal Met		·
Color: Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		
Housing design: (19") 48.3 cm rack installation 2 U Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Material:	Metal
Dimensions: Width: 48,3 cm Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Color:	Black
Depth: 40 cm Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Housing design:	(19") 48.3 cm rack installation 2 U
Height: 8,9 cm Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Dimensions:	Width: 48,3 cm
Weight: 12,45 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		
Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		
Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		12,45 kg
Audio player Control: IR remote control Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999		
Control: Audio player: USB + SD Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Battery:	
Audio player: Display type: LCD display Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Audio player	
Display type: Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Control:	IR remote control
Music format: MP3, WMA; FLAC, WAV Number of files: Max. 999	Audio player:	USB + SD
Number of files: Max. 999	Display type:	LCD display
	Music format:	MP3, WMA; FLAC, WAV
Available storage media: USB devices/SD cards max. 32GB (FAT 32)	Number of files:	Max. 999
	Available storage media:	USB devices/SD cards max. 32GB (FAT 32)