

## OMNITRONIC PAP-350 PA Amplifier

PA power amplifier, 350 W RMS

Art. No.: 80709810

GTIN: 4026397220896



**List price: 570.01 €**

incl. 19% VAT.

### Features:

- 1 line input (optionally XLR or 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- Load detection and power control
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

#### Package contents

- 1 x user manual, 1 x amplifier

### Logistic

EAN / GTIN: 4026397220896

Weight: 13,65 kg

Length: 0.55 m

Width: 0.48 m

Height: 0.19 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	700 W
Protection class:	Protection class I
Output power:	350 W RMS
Power connection:	Fixed power supply cord with safety plug
Device fuse:	5 x 20 mm, T 6,3 A fuse replaceable
Frequency range:	80 - 16000 Hz

S/N ratio:	>90 dB line
THD:	<0,5 % at 1 kHz
Cooling:	1 x temperature-controlled fan , air flow from front to rear
Impedance:	4-16 ohms; public address systems 100V; Public address systems 70V
Housing color:	Black
Circuitry:	Class AB
Controls:	Softstart; overheat; overload; short-circuit; DC voltage
Status LED:	Signal, power, fault, clip
Connections:	Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR 0,3 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 38,5 cm Height: 8,9 cm
Weight:	11,90 kg