

OMNITRONIC PAP-650 PA Amplifier

PA power amplifier, 650 W RMS

Art. No.: 80709820

GTIN: 4026397220902



List price: 712.81 €

incl. 19% VAT.

Features:

- 1 line input (optionally XLR or 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- Load detection and power control
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Package contents

- 1 x amplifier, 1 x user manual

Logistic

EAN / GTIN: 4026397220902

Weight: 16,80 kg

Length: 0.55 m

Width: 0.48 m

Height: 0.20 m

Technical specifications:

| | |
|-------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Protection class: | Protection class I |
| Output power: | 650 W RMS |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | 1,2 m |
| Device fuse: | 5 x 20 mm, T 8 A fuse replaceable |
| Frequency range: | 80 - 16000 Hz |

| | |
|-------------------|--|
| S/N ratio: | >90 dB line |
| THD: | <0,5 % at 1 kHz |
| Cooling: | 1 x temperature-controlled fan , air flow from front to rear |
| Impedance: | 4-16 ohms; public address systems 100V; Public address systems 70V |
| Housing color: | Black |
| Circuitry: | Class AB |
| Control elements: | Power switch, level control |
| Controls: | Softstart; overheat; overload; short-circuit; DC voltage |
| Status LED: | Signal, power, fault, clip |
| Connections: | Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR 0,3 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR Output: speaker via 4 x screw terminal |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48,3 cm Depth: 38,5 cm Height: 8,9 cm |
| Weight: | 15,00 kg |