Honeywell

HONEYWELL Column Speaker L-VOM20A/EN IP66(EN54)

Column speaker

Art. No.: 80710003

GTIN: 4026397558869

The article is no longer in our assortment.

Features:

- EN 54-16 certified and EN 60849 compliant
- 2-way coaxial system with 2 x 10 cm woofer (4")
- 100 V transformer with 4 power taps
- Intelligible voice and superior sound reproduction
- Robust aluminum enclosure, white RAL9003
- Swivel bracket
- For indoor and outdoor amplifying systems (IP66)
- EASE data available in the download section
- Suitable for outdoor use

Logistic

EAN / GTIN: 4026397558869
Weight: 4,35 kg
Length: 0.41 m
Width: 0.31 m
Heigth: 0.27 m

Technical specifications:

Power connection:	Fixed Supply cord with open wires
Power:	Program: 30W Rated: 20W RMS
Frequency range:	300 - 15000 Hz
Impedance:	Public address systems 100V
Speaker:	1 x woofer 4"
Type of speaker:	Column speaker
Dimensions:	Width: 16,5 cm Depth: 15 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Height: 34,4 cm
Weight:	3,80 kg
Input:	100 V, 70 V
Classification:	EN54-24
Woofer:	2 x 10 cm (4")
Peak power:	30 W
Maximum SPL:	94 dB
Dimensions:	165 x 150 x 344 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.