

HONEYWELL Ceiling Speaker L-VCM6A/EN (EN54)

Recessed ceiling speaker with firedome

Art. No.: 80710009

GTIN: 4026397519044



The article is no longer in our assortment.

Features:

- 2-way coaxial system with 16.5 cm woofer (6.5")
- Firedome for safety in case of fire
- Sturdy steel grille, white RAL9003
- Easy and super quick installation via clamp system
- For speech and background music in indoor PA systems
- EASE data available in the download section
- Complies with EN 54-24 and EN 60849

Logistic

EAN / GTIN: 4026397519044
Weight: 1,75 kg
Length: 0.27 m
Width: 0.27 m
Heigth: 0.17 m

Technical specifications:

Power connection:	Fixed supply cord with open wires
Power:	Program: 12W Rated: 6W RMS
Frequency range:	170 - 22000 Hz
Max. SPL:	91 dB
Impedance:	Public address systems 100V
Standard:	EN 54-24, EN 60849
Power tapping:	0,75W; 1,5W; 3W; 6W RMS via no connector/cable only switchable
Speaker:	1 x woofer 6,5"
Type of speaker:	Flush-mount speaker

Mounting dimensions:	Ø 19,5 cm
Dimensions:	Depth: 12,9 cm
	Diameter: Ø 22,2 cm
Weight:	1,50 kg