

OMNITRONIC GCA-6.560A Ceiling speaker 60W

Hi-fi ceiling mount speaker with firedome

Art. No.: 80710120

GTIN: 4026397349153











The article is no longer in our assortment.

Features:

- High performance 2-way system with 6.13 cm woofer (5") and 2" titanium coated dome tweeter for superior sound
- Wide frequency response and bass response
- For 8-ohm and 100 V systems
- Front-mounted 4-step power selector
- Seismic safety points, strain relief, loose cable ends
- Firedome for safety in case of fire
- Sturdy steel grille in white
- Easy and super quick installation via 4-point clamp system
- Incl. mounting brackets no additional accessories needed
- Pefect for amplfying conventional rooms

Technical specifications:

Frequency range:	65 - 25000 Hz
Speaker:	1 x woofer 6,5"
Dimensions:	Width: 26,1 cm
	Depth: 26,1 cm
	Height: 21,5 cm
Input:	100 V or 8 ohms
Components:	16.5 cm woofer (6.5"), 5 cm tweeter (2")
Rated power (100 V):	7.5/15/30/60 W RMS

Logistic

EAN / GTIN: 4026397349153 Weight: 9,20 kg Length: 0.32 m Width: 0.32 m Heigth: 0.64 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Rated power (8 ohms):	60 W RMS
Sensitivity:	90 dB
Maximum SPL:	109 dB
Dimensions (L x W x H):	261 x 261 x 215 mm
Weight:	3.8 kg