

OMNITRONIC WMS-5S PA Wall Speaker

2-way speaker with mount, public address systems 100V, 40 W RMS

Art. No.: 80710536

GTIN: 4026397523096



Features:

- 100 V technology with high-quality components for hifi sound
- 2-way bass-reflex system with 13 cm bass-midrange speaker (5") and 2.5 cm tweeter (1")
- Suitable for 100 V or 8-ohm operation
- 4-step power selector
- Weather-proof plastic cabinet (IP44) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket
- Loose cable ends
- For outdoor and indoor amplifying systems

Logistic

EAN / GTIN: 4026397523096

Weight: 4,25 kg

Length: 0.34 m

Width: 0.24 m

Height: 0.19 m

Technical specifications:

IP classification:	IP44
Power:	Program: 80W Rated: 40W RMS (8 ohms) Rated: 40W RMS (100V PA)
Frequency range:	70 - 20000 Hz
Sensitivity:	90 dB
Impedance:	Public address systems 100V; 8 ohms
Power tapping:	5W; 10W; 20W; 40W RMS via selector switch switchable

Speaker:	1 x woofer 5" Tweeter 1"
Type of speaker:	Compact cabinet speaker
Dimensions:	Width: 19.6 cm Depth: 15.7 cm Height: 29.5 cm
Weight:	3.70 kg

Scope of delivery:
