

OMNITRONIC WA-6S PA wall speaker/2pcs

Universal speaker system/ pair

GTIN: 4026397255775



The article is no longer in our assortment.

Description:

Due to its integrated transformators and the attractive design, this speaker series offers a perfect possibility for the use of the 100 V PA technique. The speakers are leak-proofed, so they can not be affected by humidity. All versions -from 100 over 120 and 150 Watt- are available in a classic black or an elegant looking white.

Features:

- 100 V technology with balanced frequency range and powerful sound
- 2-way system with 16.5 cm woofer (6.5") and 2.5 cm tweeter (1")
- Black or white plastic housing (ABS) with metal grille
- Connection cable with 3 power taps
- Incl. wall kit
- For indoor amplifying systems

Technical specifications:

Frequency range:	40 - 20000 Hz	
Speaker:	1 x woofer 6,5"	
Dimensions:	Width: 16 cm	
	Depth: 15 cm	
	Height: 24 cm	
Input voltage:	100 V	

Logistic

EAN / GTIN: 4026397255775 Weight: 6,90 kg Length: 0.42 m Width: 0.24 m Heigth: 0.36 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Components:	16,5 cm woofer (6,5"), 2,5 cm tweeter (1")
Rated power:	10 W RMS (yellow)
	20 W RMS (green)
	30 W RMS (red)
	COM (black)
Sensitivity:	90 dB, ±3 dB
Dimensions (H x W x D):	290 x 200 x 190 mm
Weight:	3.3 kg