

OMNITRONIC PA Volume Controller, 20 W mono bk

Mountable PA volume controller with 24 V emergency priority relay

Art. No.: 80711010

GTIN: 4026397260533



The article is no longer in our assortment.

Features:

- Audio transformer for 100 V line technique
- Attenuation in 11 steps
- Black plastic front panel and knob
- Mounting depth: 45 mm
- Screw plug connection
- Flush mounting
- Finery housing (optional)

Technical specifications:

| Priority relay: | 24 V |
|------------------|---|
| Power: | Rated: 20W RMS |
| Frequency range: | 50 - 18000 Hz |
| Input & output: | Mono |
| Housing design: | Flush mounting Finery housing (optional) |
| Dimensions: | Width: 8 cm Depth: 6,7 cm |
| | Height: 8 cm |
| Weight: | 0,18 kg |







Logistic

EAN / GTIN: 4026397260533 Weight: 0,21 kg Length: 0.09 m Width: 0.09 m Heigth: 0.09 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.