# eurolite®

### **EUROLITE LVH-7 Manual video switch**

Manual video switch 2:1



## The article is no longer in our assortment.

#### **Description:**

#### MANUAL VIDEO SWITCH 2:1

The LVH-7 is the ideal choice in installations where either a manual switch or an open-collector must switch video signals. The LVH-7 utilizes a high quality RF relay to switch one of two video sources to one output or two video sources to a single video destination. To control the LVH-7 you need the LVH-8 with open collector output or relay contacts on any other equipment. The unit is compatible with NTSC and PAL systems.

#### Features:

- Manual switching of video
- Controllable with LVH-8 or relay contacts of other units
- Switches one of two video signals to one output
- Routes one video signal between two outputs
- Remote controlled video switching
- NTSC and PAL compatible
- 12-24 V DC power supply via block terminals (PSU not included in the delivery)
- Ultra compact

#### **Technical specifications:**

Power supply:	12-24V DC 30 mA
Power connection:	Via screw terminal
Connections:	Input: video via 2 x BNC (F)

#### Logistic

EAN / GTIN: 4026397324839 Weight: 0,09 kg Length: 0.09 m Width: 0.04 m Heigth: 0.05 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Output: video via 1 x BNC (F)
Dimensions:	Width: 7,6 cm
	Depth: 4,1 cm
	Height: 3,1 cm
Weight:	0,07 kg
TRIG input current:	2 mA
TRIG input threshold:	2 V DC