

OSRAM 64841FL HALOPAR-30 240V/75W 2000h Flood E-27

PAR-30 lamp

Art. No.: 88041110 GTIN: 4050300435367



The article is no longer in our assortment.

Features:

- Halogene lamp, suitable for E-27-socket (230 V~)
- Clear, brilliant halogene light for spot (10°) or Flood (30°)
- Operation at mains voltage without transformator
- Front screen provides for low bleaching and protects against contact with and soiling of burner
- Easy replacement with normal E-27 reflector lamps
- Average lifetime 2000 hours
- Constant light flow and no blackening of the burner during lifetime
- Any burner position possible
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Voltage (lamps):	230 V, AC
Nominal wattage:	75 W
Base:	E27
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; reflector lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike

Logistic

EAN / GTIN: 4050300435367 Weight: 0,18 kg Length: 0.09 m Width: 0.09 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Beam angle:	30°
Color of light:	White
Color temperature:	2900K
Color rendering index (CRI):	100 Ra
Lead time:	0 s
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	10° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	650 lm
Dimensions (LxD):	92x95 mm
Weight:	0,15 kg
Legal specifications	
Energy efficiency class (A++ - E):	D