OMNILUX[®]

OMNILUX PAR-64 240V/500W GX16d MFL 300h T

PAR-64 lamp (Tungsten)

Art. No.: 88145206 GTIN: 4026397150537



The article is no longer in our assortment.

Features:

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For application areas such as: Video and photography; Clubs/dancing school; Stage

Technical specifications:

| Operating voltage: | 240 V, 220 - 240 V |
|------------------------------|--|
| Nominal wattage: | 500 W |
| Base: | GX16d |
| Lamp type: | Halogen lamp; clear lamp; high voltage lamp; sealed beam lamp; halogen bulb |
| Lamp specification: | Dimmable |
| | Hot restrike |
| Beam angle: | 21° |
| Color of light: | White |
| Color temperature: | 2700K |
| Color rendering index (CRI): | 95 Ra |
| | |

Logistic

EAN / GTIN: 4026397150537 Weight: 0,99 kg Length: 0.17 m Width: 0.17 m Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Lead time: | 0 s |
|-----------------------------|--|
| Construction: | PAR-64 |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 300 h |
| Luminous flux: | 5500 lm |
| Dimensions (LxD): | 152x203 mm |
| Weight: | 840 g |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |