# **OMNILUX**®

### OMNILUX MR-11 12V/15W G-4

Cool-beam mirrored lamp

Art. No.: 88212009 GTIN: 4026397461466



## The article is no longer in our assortment.

#### Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long lifetime (average lifetime 1000 h)
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

#### **Technical specifications:**

Operating voltage:	12 V
Nominal wattage:	15 W
Base:	G-4
Lamp type:	Halogen lamp; clear lamp; low voltage lamp; halogen bulb

#### Logistic

EAN / GTIN: 4026397461466 Weight: 0,02 kg Length: 0.04 m Width: 0.04 m Heigth: 0.04 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp specification:	Dimmable Hot restrike
Beam angle:	25°
Color of light:	White
Color temperature:	3000K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	1000 h
Luminous flux:	110 lm
Dimensions (LxD):	37x35,5 mm
Weight:	20 g
Legal specifications	
Energy efficiency class (A++ - E):	D