

PHILIPS MSD250/2 90V/250W GY-9.5 3000h

HMI / MSR / HMP / OMI lamps

Art. No.: 89106115 GTIN: 08727900915693



List price: 201.11 €

incl. 19% VAT.

Description:

Basics:

GS=Gap Short (shortened electrode space) DE=Double Ended (double-sided lamp with threaded pin) SE=Single Ended (one-sided lamp) PAR=Lamp built in a parabolic reflector HMP=Due to their special filling and to their electrode system, HMP-lamps cannot only be "dimmed", but also be "boosted", i. e. be operated beyond their rated power. During this, the light technical characteristics, such as color temperature, color rendering index and light output are practically constant during "dimming" and "boosting".

Features:

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Operating voltage:

90

Logistic

EAN / GTIN: 08727900915693 Weight: 0,06 kg Length: 0.16 m Width: 0.09 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

250 W
GY9.5
Discharge lamp
8500K
S180 (universal)
3000 h
18000 lm
3 A
108x23 mm
0,04 kg
Not designed for household room illumination
Show effect lighting