



The article is no longer in our assortment.

Description:

Basics:

GS=Gap Short (shortened electrode space)

DE=Double Ended (double-sided lamp with threaded pin)

SE=Single Ended (one-sided lamp)

PAR=Lamp built in a parabolic reflector

HMP=Due to their special filling and to their electrode system, HMP-lamps cannot only be "dimmed", but also be "boosted", i. e. be operated beyond their rated power. During this, the light technical characteristics, such as color temperature, color rendering index and light output are practically constant during "dimming" and "boosting".

Logistic

EAN / GTIN: 4026397106527

Weight: 0,09 kg

Length: 0.16 m

Width: 0.05 m

Height: 0.05 m

Features:

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight (between 4500 and 6500 K)
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps

Technical specifications:

Operating voltage:

95 V

| | |
|----------------------|--|
| Nominal wattage: | 575 W |
| Base: | GX9.5 |
| Lamp type: | Metal vapour lamp |
| Color temperature: | 6000K |
| Burning position: | S180 (universal) |
| Lamp life: | 750 h |
| Luminous flux: | 49000 lm |
| Dimensions (LxD): | 125x28 mm |
| Weight: | 60 g |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |