

OMNILUX OMI 1200 100V/1200W SFC-15 400h

HMI / MSR / HMP / OMI lamps

Art. No.: 89302005

GTIN: 4026397136562



List price: 53.43 €

incl. 19% VAT.

Description:

Basics:

GS=Gap Short (shortened electrode space)

DE=Double Ended (double-sided lamp with threaded pin)

SE=Single Ended (one-sided lamp)

PAR=Lamp built in a parabolic reflector

HMP=Due to their special filling and to their electrode system, HMP-lamps cannot only be "dimmed", but also be "boosted", i. e. be operated beyond their rated power. During this, the light technical characteristics, such as color temperature, color rendering index and light output are practically constant during "dimming" and "boosting".

Logistic

EAN / GTIN: 4026397136562

Weight: 0,12 kg

Length: 0.29 m

Width: 0.04 m

Height: 0.04 m

Features:

HMI / MSR / HMP / OMI lamps

- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNILUX OBA 1200 100V/1200W SFC-15 5600K

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Constant color temperature and color rendering behaviour over the whole lamp life

- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Good color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Lamp type:	Metal vapour lamp
Lamp specification:	Hot restrike
Construction:	Double-sided socket
Burning position:	S180 (universal)
Weight:	120 g
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX OBA 1200 100V/1200W SFC-15 5600K

Operating voltage:	100 V
Nominal wattage:	1200 W
Base:	SFC15
Lamp type:	Metal vapour lamp
Lamp specification:	Hot restrike
Color temperature:	5600K
Color rendering index (CRI):	80 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	750 h
Luminous flux:	110000 lm
Dimensions (LxD):	220x28 mm
Weight:	120 g
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting