OMNILUX[®]

OMNILUX OBA 1200 100V/1200W SFc-15 5600K

HMI / MSR / HMP / OMI lamps



The article is no longer in our assortment.

Description:

Let there be light!

Allthough you might not expect it, but not all products produced these days come from China. As counter-example we would like to introduce our new OMNILUX OBA lamps. They are produced in belgium and do meet the highest quality standards and are available for immediate delivery. They will be blinding good times.

Features:

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Good color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:	
Operating voltage:	100
Nominal wattage:	1200 W

Logistic

EAN / GTIN: 4026397297874 Weight: 0,28 kg Length: 0.30 m Width: 0.08 m Heigth: 0.08 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Base:	SFc15
Lamp type:	Metal vapour lamp; discharge lamp
Lamp specification:	Hot restrike
Color temperature:	5600K
Color rendering index (CRI):	80 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	750 h
Luminous flux:	110000 lm
Lamp current:	13,8 A
Dimensions (LxD):	220x28 mm
Weight:	0,12 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting