

OMNILUX MR-16 12V/75W GX-5.3 FL 36° EYC

Cool-beam mirrored lamp

Art. No.: 91205700

GTIN: 4026397099362



The article is no longer in our assortment.

Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long lifetime (average lifetime 2000 h)
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397099362

Weight: 0,04 kg

Length: 0.05 m

Width: 0.05 m

Heigh: 0.05 m

Technical specifications:

Operating voltage: 12 V

Nominal wattage: 75 W

Base: GX5.3

| | |
|------------------------------------|--|
| Lamp type: | Halogen lamp; clear lamp; low voltage lamp; sealed beam lamp; halogen bulb; Cool Beam lamp |
| Lamp specification: | Dimmable Hot restrike |
| Beam angle: | 36° |
| Color of light: | White |
| Color temperature: | 2600K |
| Color rendering index (CRI): | 95 Ra |
| Lead time: | 0 s |
| Construction: | MR-16; Reflector; Bi pin |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 2000 h |
| Dimensions (LxD): | 81x51 mm |
| Weight: | 30 g |
| Legal specifications | |
| Energy efficiency class (A++ - E): | D |