

OMNILUX MR-16 24V/75W GX-5.3 SP 38° EYC

Cool-beam mirrored lamp

Art. No.: 91205802 GTIN: 4026397343465



## The article is no longer in our assortment.

## Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long life
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

## **Technical specifications:**

Voltage (lamps):	24 V, AC
Nominal wattage:	75 W
Base:	GX5.3
Lamp type:	Halogen lamp; clear lamp; low voltage lamp; reflector lamp; halogen bulb; cool Beam lamp

## Logistic

EAN / GTIN: 4026397343465 Weight: 0,03 kg Length: 0.04 m Width: 0.04 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp specification:	Dimmable Hot restrike	
Beam angle:	38°	
Color of light:	White	
Color temperature:	2500K	
Color rendering index (CRI):	95 Ra	
Lead time:	0 s	
Construction:	MR-16; reflector; bi pin	
Operating temperature max.:	40° C	
Operating temperature min.:	20° C	
Burning position:	S180 (universal)	
Lamp life:	2000 h	
Dimensions (LxD):	81x51 mm	
Weight:	0,02 kg	
Legal specifications		
Energy efficiency class (A++ - E):	D	