



### Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long lifetime (average lifetime 2000 h)
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

### Logistic

EAN / GTIN: 4026397343526

Weight: 0,04 kg

Length: 0.04 m

Width: 0.04 m

Heigh: 0.06 m

### Technical specifications:

Voltage (lamps): 24 V, AC

Nominal wattage: 35 W

Base: GX5.3

Lamp type: Halogen lamp

Lamp specification: Dimmable

---

Hot restrike

---

Beam angle:	38°
Color of light:	White
Color temperature:	2500K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	MR-16; reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Dimensions (LxD):	81x51 mm
Weight:	0.03 kg
Energy efficiency class (A++ - E):	D

---

**Scope of delivery:**

---