



Caractéristiques:

FUTURELIGHT LED PXS-20 Artnet Strip

LED bar for video and pixel mapping applications via Art-Net

- Modular LED strip with 20 pixels for video and pixel mapping applications via Art-Net
- Data and power supply via optional video processor
- Extra bright and colorful projection of videos, animations and graphics
- Modular concept allows the build-up of large areas
- Ideal for rental companies, stage/fair construction and fixed installation
- For use with MADRIX or any other lighting control software supporting Art-Net
- RGB SMD 5050 LEDs, covered by a smooth diffuser plate, provide excellent color rendering and wide viewing angles
- Signal distribution via UTP cable
- Movable mounting bracket for flexible installation
- 20 LED SMD 5050 3in1 R/G/B (mélange de couleurs homogène)
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via RDM; Art-Net
- Avec un Angle de départ de 120°

FUTURELIGHT PSU-16 Artnet Controller

Video processor for LED PXS-40 + PXS-20 Art-Net Strip

- Video processor and power supply unit for LED PXS-40/20 Artnet Strip
- For use with MADRIX or any other lighting control software supporting Art-Net
- Connections for 16 LED PXS-40 Artnet Strips
- 2 x 16-digit LCD screen for menu settings
- Integrated web interface for comfortable configuration and firmware updates through a browser

Logistique

- Useful software tool scans the network and identifies fixtures
- Neutrik PowerCon input and output
- Signal distribution via UTP cable
- Switch-mode power supply for operation between 100 and 240 volts
- Commandé via Art-Net; RDM

Données techniques:

Poids: 44,35 kg

FUTURELIGHT LED PXS-20 Artnet Strip

Alimentation électrique:	28V CC
Puissance totale de raccordement:	10,00 W
Type de lampe:	Lampe LED
Type de LED:	20 x SMD 5050 3in1 R/G/B (mélange de couleurs homogène)
Canaux DMX:	60
Connexion au réseau:	Protocole : Art-Net 3 via 2x RJ-45 (F) version encastrable
Refroidissement:	Refroidissement par convection passive
Commande:	RDM; Art-Net
Angle de départ (1/2 pic):	120°
Image:	20 px Distance entre les pixels 25 mm Luminosité 850%cd/m ²
Couleur du boîtier:	Noir
Dimension:	Longueur : 50 cm Profondeur : 3,8 cm Hauteur : 14 cm
Poids:	1,30 kg
Display refresh rate:	400 Hz
Video refresh rate:	60 fps
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

FUTURELIGHT PSU-16 Artnet Controller

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	300,00 W
Connexion au réseau:	Protocole : Art-Net 3 via 2x RJ-45 (F) version encastrable
Commande:	Art-Net; RDM
Couleur du boîtier:	Noir
Connexions:	Signal via 4 x RJ-45 (F) version encastrable

