

## OMNITRONIC MX-540 Multichannel mixer

PRO 5+1-channel mixer

Réf. : 10006760

GTIN: 4026397361193



### Caractéristiques:

- High-grade discotheque mixer with convincing sound and 3 master channels
- 5 channels with gain control, 3-band equalizer, cue button, smooth and durable faders and 10-digit LED level meter
- 1 DJ microphone channel with 3-band equalizer, level control, on air and talkover selector
- Color illuminated rotary controls and rubber buttons
- Prefader listening to all input channels and the master output via adjustable headphones output, with cue mix/split function
- Replaceable crossfader for crossfading between input channels, with assignment switches and fader start function
- 3 separately controllable master channels with mono/stereo selector switch
- Master channel 1 with fader and 10-digit stereo LED level meter, switchable to master channel 2
- Adjustable monitor output (DJ booth)
- 2 recording outputs, independent of the master and with on/off switch for DJ microphone signals
- Inputs: 12 x line (stereo RCA), additionally 1 x line at the front panel (stereo RCA/3.5 mm jack (1/8")); 3 x phono/line (stereo RCA), switchable; 1 x DJ microphone (XLR/6.3 mm jack), 3 x microphone (6.3 mm jack) and headphones (3.5 mm/6.3 mm jack (1/8"/1/4"))
- Outputs: 2 x master (stereo XLR/stereo RCA), 1 x master (stereo RCA/6.3 mm stereo jack, bal.), booth (stereo RCA) and 2 x record (stereo RCA)
- Operation via supplied power unit
- Available in silver or black
- Rack installation, 5 U
- (19") 48,3 cm installation en rack

### Logistique

EAN / GTIN: 4026397361193

Poids: 6,10 kg

Longueur: 0.61 m

Largeur: 0.27 m

Hauteur: 0.15 m

## Données techniques:

|                                   |   |
|-----------------------------------|---|
| Puissance totale de raccordement: | 30,00 W   |
| Plage de fréquence:               | 20 - 20000 Hz   |
| Conception du boîtier:            | (19") 48,3 cm installation en rack                          |
| Dimension:                        | Largeur : 48,3 cm<br>Profondeur : 22 cm<br>Hauteur : 8,9 cm |
| Poids:                            | 5,55 kg   |
| Power supply:                     | 230 V AC, 50 Hz,<br>via supplied power unit                 |
| Inputs:                           |   |
| DJ microphone (front):            | combined XLR/6.3 mm jack (1/4") (bal.)                      |
| DJ microphone (rear):             | 6.3 mm jack (1/4") (bal.)                                   |
| MIC 1-3:                          | 6.3 mm jack (1/4") (bal.)                                   |
| Minimum input voltage:            | 1 mV RMS  |
| LINE 1-12 (rear):                 | stereo RCA  |
| LINE 10 (front):                  | stereo RCA/3.5 mm jack (1/8")                               |
| Minimum input voltage:            | 150 mV RMS  |
| PHONO 1-3:                        | stereo RCA  |
| Minimum input voltage:            | 3 mV RMS  |
| Outputs:                          |   |
| MASTER 1.2:                       | stereo XLR/stereo RCA                                       |
| Output voltage:                   | 0.75 V/1.5 V RMS (switchable)                               |
| MASTER 3:                         | stereo RCA/6.3 mm stereo jack                               |
| Output voltage:                   | 0.75 V  |
| BOOTH:                            | stereo RCA  |
| Output voltage:                   | 0.75 V  |
| REC:                              | stereo RCA  |
| Output voltage:                   | 0.75 V  |
| Headphones output:                | 3.5 mm/6.3 mm jack (1/8"/1/4") (min. 8 ohms)                |
| X-FADER START:                    | 2 x 3.5 mm jack (1/8")                                      |
| Tone control (DJ microphone):     |   |
| 1 x High:                         | -12 dB to +12 dB/ 10 kHz, ±1 dB                             |
| 1 x Middle:                       | -12 dB to +12 dB/ 1 kHz, ±1 dB                              |
| 1 x Low:                          | -12 dB to +12 dB/ 100 Hz, ±1 dB                             |
| Talkover attenuation:             | -15 dB  |
| Tone control (channel 1-5):       |   |
| 5 x High:                         | -26 dB to +12 dB/ 10 kHz, ±1 dB                             |
| 5 x Middle:                       | -26 dB to +12 dB/ 1 kHz, ±1 dB                              |
| 5 x Low:                          | -26 dB to +12 dB/ 100 Hz, ±1 dB                             |
| S/N ratio:                        | >75 dB  |
| Distortion:                       | 0.03%   |

Dimensions (WxHxD):

482 x 220 x 110 mm (19", 5 U)

---

**Contenu de la livraison:**

---