

## OMNITRONIC EM-550B Entertainment Mixer

Mixeur d'installation multifonctionnel 5 + 2 canaux, noir

Réf. : 10007101

GTIN: 4026397466423



### Caractéristiques:

- 5 input channels with recessed gain controls on the rear panel, signal LED and super smooth dual-rail channel faders
- 2 separate microphone channels with level control, 3-way equalizer and talkover button
- Talkover level and response time adjustable
- Pre-fader listening (CUE) to the stereo input channels via adjustable headphone output
- Color illuminated rotary controls and rubber buttons
- 1 additional line input with level control on the front panel
- 2 adjustable master outputs with 3-way equalizer and 10-digit stereo LED level meter
- 1 adjustable booth output with mono/stereo selector switch
- 2 record outputs (independent of the master channels) with on/off switch for microphone signals
- Inputs: 9 x line (stereo RCA), 2 x line/phono (stereo RCA), switchable; 2 x microphone (XLR/6.3 mm jack) and headphones (6.3 mm jack)
- Outputs: 2 x master (optionally 3-pin XLR or stereo RCA), 1 x booth (stereo RCA) and 2 x record (stereo RCA)
- Operation via supplied power unit
- Rack installation, 2 U
- Ideal for restaurants, bars, theme parks, hotels and all applications where microphones need to be mixed with music (e.g. karaoke)
- (19") 48,3 cm installation en rack 2 HE

### Logistique

EAN / GTIN: 4026397466423

Poids: 4,25 kg

Longueur: 0.61 m

Largeur: 0.16 m

Hauteur: 0.14 m

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 35,00 W

Branchement électrique:	Alimentation électrique via connecteur fileté (M) IP 3 broches version encastrable câble d'alimentation à prise euro (inclus dans la livraison)
	Tramite
Plage de fréquence:	20 - 20000 Hz
Rapport signal/bruit:	>65 dB
Égaliseur:	Master: 2 x régulateur 3 bandes Stéréo
Conception du boîtier:	(19") 48,3 cm installation en rack 2 HE
Dimension:	Largeur : 48,3 cm Profondeur : 11,5 cm Hauteur : 8,9 cm
Poids:	3,80 kg
Inputs:	
Microphone 1.2	combined XLR/6.3 mm jack (1/4") (bal.)
Minimum input voltage:	1 mV RMS
Line 1-8, Aux 1.2:	stereo RCA
Minimum input voltage:	150 mV RMS
Phono 1.2:	stereo RCA
Minimum input voltage:	3 mV RMS
Outputs:	
Master 1.2:	stereo RCA, stereo XLR
Output voltage:	0.75 V/1.5 V RMS (switchable)
Booth:	stereo RCA (switchable to mono operation)
Output voltage:	0.75 V RMS
Record:	stereo RCA
Output voltage:	0.75 V RMS
Headphones output:	6.3 mm stereo jack (min. 8 ohms)
Tone control (microphone 1.2; output 1.2):	
4 x High:	-12 dB to +12 dB/ 10 kHz
4 x Mid:	-12 dB to +12 dB/ 1 kHz
4 x Low:	-12 dB to +12 dB/ 100 Hz
Talkover attenuation:	-15 dB
Distortion:	0.03 %
Dimensions (WxHxD):	483 x 115 x 90 mm (19", 2 U)

## Contenu de la livraison: