OMNITRONIC LH-081 Stereo isolator RCA

Isolateur de ligne stéréo passif à connecteurs RCA

Réf. : 10355081

GTIN: 4026397301991

L'article n'est plus disponible.

Description:

Goodbye to growlers!
Working in a field that is technical and complex such as stereo equipment, disorders cannot always be prevented and often happen to be on the agenda. A frequently occurring problem: the so called hums. They come up when a notebook is linked to a PA-system. The easiest and fastest solution is offered by our LH-081. Simply plug it in and the annoying humming will immediately belong to history. You can really trust in our line isolator with its rugged metal housing.

Caractéristiques:

- Passive stereo line isolator
- For avoiding signal interference and ground loop problems
- Galvanic isolation of inputs and outputs
- Two high-quality audio transformers
- All connections via RCA connectors
- Rugged metal housing

Données techniques:

Plage de fréquence:	15 - 30000 Hz
Dimension:	Largeur : 11 cm Profondeur : 4 cm Hauteur : 7,5 cm

Logistique

EAN / GTIN: 4026397301991
Poids: 0,53 kg
Longueur: 0.23 m
Largeur: 0.13 m
Hauteur: 0.08 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Poids:	380 g
Connections:	RCA
Input impedance:	600 ohms
Output impedance:	600 ohms
S/N ratio:	>95 dB

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.