

OMNITRONIC XO-23B Active crossover

Répartiteur actif, stéréo 2 canaux et mono 3 canaux

Réf. : 10355626

GTIN: 4026397385380



Caractéristiques:

- 2-way stereo or 3-way mono operation possible
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 45 Hz to 9.5 kHz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low cut switch
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistique

EAN / GTIN: 4026397385380

Poids: 2,45 kg

Longueur: 0.54 m

Largeur: 0.20 m

Hauteur: 0.08 m

Données techniques:

| | |
|-----------------------------------|--|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 10,00 W |
| Dimension: | Largeur : 48,3 cm Profondeur : 14,7 cm Hauteur : 4,45 cm |
| Poids: | 2 kg |
| Slope: | 24 dB / octave |
| Operation modes: | 2-way stereo or 3-way mono |

| | |
|-------------------------|---------------------------|
| Input: | Mono/stereo |
| Input impedance: | 10/20 kohms (unb./bal.) |
| Output: | Mono/stereo |
| Output impedance: | 300/150 kohms (unb./bal.) |
| In/Out connectors: | XLR |
| S/N ratio: | >100 dB |
| Xover frequency range: | 45-9500 Hz |
| THD: | 0.05% |
| Crosstalk: | >80 dB, -3 dB |
| Input gain: | - ~ to + 6 dB |
| Control range: | - ~ to + 12 dB |
| Low Cut: | 30 Hz, -3 dB |
| Phase adjustment: | 0-180° |
| Dimensions (W x D x H): | 483 x 147 x 46 mm |

Contenu de la livraison:
