

## PSSO DXO-48 Digital system controller

Processeur de diffusion d'enceinte numérique à 4 entrée et 8 sorties, avec logiciel

Réf. : 10356360

GTIN: 4026397195590



## L'article n'est plus disponible.

### Description:

Active speaker-management, getting along without compromises. Whether via the included software or directly on the device, the DXO-48 offers intuitive operation and flexible signal-routing - at an unbeatable value for money. Even multiple units in comprehensive fixed installations can be comfortably managed, thanks to the clearly structured software. The push buttons on the controller allow direct addressing of all inputs and outputs, making editing fast and simple via the large display. An advantage especially for live use: last setup modifications can be easily adjusted without a computer.

### Caractéristiques:

- 4 inputs and 8 outputs with flexible signal routing
- 32-bit floating point DSP
- 96 kHz sampling rate
- 24 bit A-D/D-A-converter
- 6 fully parametric equalizers per input and output
- Slopes up to 48 dB/octave
- Backlit 4 lines x 20 character display
- 30 user programs can be memorized
- Up to 500 ms signal delay for the inputs and outputs adjustable
- Delay displayed in milliseconds, meters, feet and frame/second
- Output limiter with adjustable limits and automatic attack and release settings as overload protection for your amplifying system
- Lock-function for protecting the program settings
- Phase Invert per output
- Digital adjustment of the input gain  $\pm 15$  dB

### Logistique

EAN / GTIN: 4026397195590

Poids: 4,85 kg

Longueur: 0.61 m

Largeur: 0.36 m

Hauteur: 0.08 m

- Vous trouverez de plus amples informations sur ce produit dans la rubrique  
« Téléchargements » de la fiche technique

## Données techniques:

Alimentation électrique:	115/230 V CA, 50/60 Hz
Puissance totale de raccordement:	30,00 W
Connexions:	Entrée: 4 x Sortie: 8 x
Dimension:	Largeur : 48,3 cm Profondeur : 20 cm Hauteur : 4,45 cm
Poids:	3 kg
Inputs:	4, active, balanced
Gain range:	-40 to +15 dB
Input impedance:	10 kohms
Frequency range:	15-20000 Hz, $\pm 0.25$ dB 15-40000 Hz, $\pm 3$ dB
Outputs:	8, active, balanced with automatic correction for unbalanced loading
Output impedance:	<50 mohms (electronically balanced)
Output gain range:	$\pm 21$ dB
Maximum output level:	+20 dBu
Frequency range:	20-20000 Hz, $\pm 0,1$ dB 15-40000 Hz, $\pm 3$ dB
Distorsion:	0.001 % (1 kHz @ 18 dBu)
S/N-ratio:	115 dB
Channel separation:	<-100 dB
Slopes:	6, 12, 18, 24 or 48 dB/Oktave
Type:	Bessel, Butterworth or Linkwitz-Riley
Crossover frequency:	20-20000 Hz
Delay:	0~0.45 s
Dimensions (WxHxD):	482 x 44 x 200 mm