

## OMNITRONIC ADI-002PL Interface

USB audio interface for digital recordings from line and phono sources, incl. audio software

Réf. : 10359825

GTIN: 4026397397239



### Caractéristiques:

- Plug & play audio interface connects line and phono inputs with your computer for recording and playback
- Incl. audio software Audacity for recording and editing on CD-ROM
- Directly compatible with PC and Mac - no setup required
- High-resolution 16-bit/ 48 kHz converter for high-end audio quality
- Line/phono input (stereo RCA), switchable
- Adjustable input sensitivity
- Signal/clip LED
- Line output (stereo RCA) for PA applications
- Powered via USB - no additional power supply required
- Works with any customary software for PC and Mac

### Logistique

EAN / GTIN: 4026397397239

Poids: 0,25 kg

Longueur: 0.23 m

Largeur: 0.16 m

Hauteur: 0.06 m

### Données techniques:

Plage de fréquence:	20 - 20000 Hz
Dimension:	Largeur : 10,7 cm Profondeur : 3 cm Hauteur : 11,5 cm
Poids:	0,18 kg
Power supply:	5 V DC via USB port
Distortion:	<0.05 % (line), <0.08 % (phono)
S/N ratio:	<75 dB (line), <70 % (phono)

Channel separation:	<70 dB
Inputs:	1 x line/phono (stereo RCA)
Impedance/sensitivity:	10 kohms/800 mV (line), 47 kohms/19 mV (phono)
Outputs:	1 x line (stereo RCA)
USB connection:	type A, USB 1.1
AD/DA converter:	16 bits
Sampler frequency:	48 kHz
Cable length:	1.4 m
Required operating system:	Windows 98 SE/ME/2000/XP/Vista/7/8, Mac OS X

---

**Contenu de la livraison:**

---