

## OMNITRONIC L-800, Amplifier 2x400W/4 ohm

Reliable PA amplifier for starters

Réf. : 10450680

GTIN: 4026397243086



**L'article n'est plus disponible.**

### Caractéristiques:

- 2 x 400 W/4 ohms
- Enormous power with highest brilliance
- 2 gain controls on the frontpanel
- All operation modes controllable via LEDs
- Signal inputs via XLR female or 6.3 mm jack socket
- Speaker connection via lockable Speaker plugs
- Ground lift switch against humming
- Bridged switch for bridging
- Protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation

### Logistique

EAN / GTIN: 4026397243086

Poids: 11,50 kg

Longueur: 0.50 m

Largeur: 0.43 m

Hauteur: 0.10 m

### Données techniques:

Puissance totale de raccordement:	1250,00 W
Puissance de sortie:	200 W RMS (8 Ohm)
Plage de fréquence:	10 - 50000 Hz
Dimension:	Largeur : 48,3 cm Profondeur : 35 cm Hauteur : 4,45 cm
Poids:	10,30 kg
Power supply:	115/230 AC V AC, 50/60 Hz

Power output (RMS):

Stereo 4 ohms	2 x 400 W
Stereo 8 ohms	2 x 200 W
8 ohms bridged	1 x 800 W
Signal-to-noise ratio:	>100 dB
Total harmonic distortion:	0.05 %
Damping factor:	>150
Slew rate:	70 V/ $\mu$ sec.
Crosstalk:	>70 dB
Input impedance:	20 kohms
Input connectors:	2 x XLR, 2 x Jack mounting socket
Output connectors:	2 x Speaker
Protection:	Overheat, overload, short-circuit, DC, softstart
Cooling:	Temperature-controlled fan
Controls:	Power switch, input attenuators, Mode switch - Stereo/Parallel/Bridged, Ground Lift
Indicators:	Power, Clip, Protect, Parallel, Bridge
Construction:	Steel chassis, aluminum front panel
	Rack installation with 1 u