

OMNITRONIC P-500 Amplifier, 2x250W/4 ohms

Powerful PRO amplifier

Réf. : 10451130

GTIN: 4026397135558



L'article n'est plus disponible.

Caractéristiques:

- 2 x 250 W/4 ohm
- Enormous power with highest brilliance
- 2 gain controls on the frontpanel
- All operation modes controllable via LEDs
- LED intensity adjustable via brightness control on the rear panel
- Signal inputs via XLR female or 6.3 mm jack socket
- Input sensitivity adjustable via selector on the rear panel
- Speaker connection via lockable Speaker plugs or Banana/screw combination
- With limiter
- Ground Lift switch against humming
- Bridged switch for bridging
- Many protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation
- High power/weight-relation

Logistique

EAN / GTIN: 4026397135558

Poids: 12,35 kg

Longueur: 0.51 m

Largeur: 0.48 m

Hauteur: 0.14 m

Données techniques:

Alimentation électrique: 115/230 V CA, 50/60 Hz

Puissance totale de raccordement: 1000,00 W

Puissance de sortie: 130 W RMS (8 Ohm)

Plage de fréquence: 22 - 31000 Hz

Dimension: Largeur : 48,3 cm

Profondeur : 44,5 cm
Hauteur : 8,9 cm

| | |
|--------------------------------------|--|
| Poids: | 11,15 kg |
| Power range: | 230 V \pm 10 % (207-253 V) |
| Momentary music peak power at 1 kHz: | 650 W / 4 ohms |
| Maximum power output: | 2 x 295 W / 4 ohms |
| Nominal power output: | 2 x 250 W / 4 ohms |
| Power output sine: | |
| Stereo 4 ohms | 2 x 250 W |
| Stereo 8 ohms | 2 x 130 W |
| 8 ohms bridged | 1 x 500 W |
| Damping factor: | >150 |
| Distortion factor: | 0.01 % |
| Signal-to-noise ratio: | 108 dB |
| Channel separation (at 1 kHz): | 89 dB |
| Min. input sensitivity: | 0.77 V/26 dB/1.44 V |
| Input impedance: | 12 kohms (unbalanced), 22 kohms (balanced) |
| Output impedance: | >0.02 ohms |
| Slew rate: | >30 V/ μ sec |
| Input connectors: | 2 x XLR female plug, 2 x 6.3 mm jack plug |
| Output connectors: | 2 x Speaker (stereo), 1 x Speaker (bridge), 2 x Banana/screw combination |
| Control elements: | Power switch, input attenuators (one per channel), Mode switch - Stereo/Parallel/Bridged, Ground Lift, Input-Level-Select (0.77 V/26 dB/1.44 V), limiter |
| LED indicators (per channel): | Power, Protect, Signal, Mode |
| Protection circuits: | Short-circuit, DC, thermal, softstart |
| Construction: | Steel chassis, aluminum front panel |
| Minimum mounting depth: | 460 mm |
