

OMNITRONIC DD-5250 Turntable sil

Direct drive DJ turntable "Ultra Torque"

Réf. : 10603004

GTIN: 4026397071863



Caractéristiques:

- Direct drive high-torque motor
- Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control $\pm 10\%$, $\pm 20\%$, $\pm 50\%$
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes slipmat and RCA cable
- Delivery without dust cover and pick-up system

Logistique

EAN / GTIN: 4026397071863

Poids: 12,80 kg

Longueur: 0.52 m

Largeur: 0.42 m

Hauteur: 0.18 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 15,00 W

Plage de fréquence: 20 - 20000 Hz

Dimension:	Largeur : 45 cm Profondeur : 35,3 cm Hauteur : 15,6 cm
Poids:	11 kg
Type:	3-speed full manual turntable
Drive method:	Quartz-controlled direct drive
Motor:	Brushless DC motor
Turntable platter:	d=332 mm, 1400 g
Speed:	33 1/3 RPM, 45 RPM and 78 RPM
Speed change time:	<1 sec
Rotation direction:	Forwards/backwards
Pitch adjustment:	±10 %, ±20 %, ±50 %
Initial torque:	>4.5 kg/cm
Wow and flutter:	0.1 % WRMS at 33 1/3 RPM
Adjustable start time:	0.2-6 sec
Adjustable brake time:	0.2-6 sec
Rumble:	60 dB DIN B
Tonearm:	S-shape with Cardan's suspension
Tonearm length:	230 mm
Adjustable tonearm height:	8-10.5 mm
Overhang:	15 mm
Adjustable stylus pressure	2-5 g
Anti-skating range:	0-3 g
Connectors:	Stereo RCA
Dimensions:	450 x 353 x 156 mm

Contenu de la livraison: