

OMNITRONIC Haut-parleur MAXX-1508 à 2 voies 2x

2 x enceintes large bande passives 8", 150 W RMS

Réf. : 11038833

GTIN: 4026397658064



Prix de catalogue: 343.91 €

TVA 19% incl.

Description:

The MAXX-1508DSP is an active 2.1 PA system with 700 watts output power. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 15" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 8" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1508DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1508DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

Caractéristiques:

- Système bass-reflex à 2 voies avec haut-parleur médium 8" et driver de compression 1"
- Forment un système 2.1 puissant avec le subwoofer MAXX-1508
- Avec filtre passif à 2 voies, y compris protection PTC pour les aigus
- Métalgrille en noir avec mousse acoustique
- Possibilité d'utilisation: Debout; volant; monitoring; sur trépied

Logistique

EAN / GTIN: 4026397658064

Poids: 18,35 kg

Longueur: 0.53 m

Largeur: 0.32 m

Hauteur: 0.48 m

- Avec points de vol
- Poignée de transport robuste
- Pour des domaines d'application tels que: Usage portable; DJ itinérants / artistes solos; Bailleur

L'étendue des fournitures

- 2 x tête d'ampli, 2 x câble d'enceinte

Données techniques:

Capacité de charge:	Programme: 300W Nominale: 150W RMS
Plage de fréquence:	120 - 18000 Hz
Sensibilité:	92 dB
Pression acoustique max.:	116 dB
Dispersion:	90° x 60°
Impédance:	4 Ohm
Points d'accroche:	5 x Filetage M8
Connexions:	Entrée: Enceinte via 1 x Boîtier d'enceinte encastrable (F)
Enceinte:	1 x Boumeur 8" 1 x Pilote de compression aigus 1"
Type d'enceinte:	Boîtier compact
Poignée de transport:	1 Pièce
Matériau:	MDF (panneaux de fibres à densité moyenne), 16 mm
Dimension:	Largeur : 25,5 cm Profondeur : 24,1 cm Hauteur : 42,1 cm
Poids:	17,25 kg