

## OMNITRONIC ASS-1023 Active system

Powerful mobile column PA system, 600 W RMS

Réf. : 11038852

GTIN:



### Caractéristiques:

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in time
- Convinces with excellent speech reproduction and wide coverage
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (400 W + 200 W RMS) with SMPS
- 2 x 25 cm bassreflex subwoofer
- Fullrange column speaker with 12 x 8 cm drivers
- Balanced 6.3 mm jack input and parallel XLR output
- Master level control with peak indication
- Adjustable crossover frequency for subwoofer
- Phase switchable for subwoofer
- Subwoofer with plywood enclosure
- Column speaker with MDF enclosure
- Scratch-resistant lacquer surface, impact-resistant steel grille and flange
- Delivery includes distance tube, speaker cable and power cable
- Castor set and wheel board available as accessory

### Logistique

### Données techniques:

Poids:	36,70 kg
Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	200 W (1/8 power)
Power output sine:	

Subwoofer:	400 W RMS
Satellite speaker:	200 W RMS
Components:	
Subwoofer:	2 x 25 cm woofer (10")
Satellite speaker:	12 x 8 cm mid-high driver (12 x 3")
Maximum SPL:	
Subwoofer:	120 dB
Satellite speaker:	118 dB
Frequency range:	
Subwoofer:	45-180 Hz
Satellite speaker:	120-20000 Hz
Crossover frequency:	40-160 Hz
Microphone input:	combination XLR/6.3 mm jack, bal.
Line input:	combination XLR/6.3 mm jack, bal. and RCA L/R
Speaker output:	1 x speaker, 4 ohms

### **Contenu de la livraison:**

---