OMNITRONIC PAM-70 Portable PA system

Portable PA system with integrated audio player

Réf. : 11038884

GTIN: 4026397426885

L'article n'est plus disponible.

Caractéristiques:

- All-in-one PA system with amplifier, 2-way speaker system, audio player with LCD and pitch adjustment for mobile applications
- Operation via mains connection or built-in rechargeable lead gel battery with up to 8 hours operating time
- Integrated automatic charging of the battery with indicator
- Easy transportation via telescopic trolley handle and 2 wheels
- Adjustable MP3 player for external USB and SD storage media
- Blue backlit LCD, pitch fader, pitch bend, single or continuous play, folder naviagation, cueing, repeat 1/all, reverse run, ID3 tag support
- 1 adjustable balanced microphone input via XLR/jack combination
- 1 adjustable instrument input (6.3 mm jack) for your guitar, keyboard, etc.
- 1 adjustable AUX input (stereo RCA) for line sources such as iPods and other MP3 players
- Link connection (6.3 mm jack) for combining several PA systems
- Housing in flightcase design with aluminum profile frames, with recessed handles
- Impact-resistant steel grille
- Speaker flange for installation on a speaker stand
- Voltage selector for power supply adaption between 115 and 230 volts
- Sans fil, flexible et polyvalent
- Durée de fonctionnement jusqu'à 8h en fonction du programme utilisé

Logistique

EAN / GTIN: 4026397426885

Poids: 15,10 kg

Longueur: 0.54 m

Largeur: 0.34 m

Hauteur: 0.44 m

Données techniques:

Alimentation électrique:	115/230 V CA, 50/60 Hz
	CA

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Puissance totale de raccordement:	70,00 W
Type de batterie:	1 x Plomb 12 V, 4500 mAh,
Batterie:	Durée de fonctionnement jusqu'à 8h en fonction du programme utilisé Durée de charge 5h
Plage de fréquence:	70 - 20000 Hz
Dimension:	Largeur : 27,5 cm Profondeur : 35 cm Hauteur : 44,5 cm
Poids:	13 kg
Power supply:	115/230 V AC, 50/60 Hz for mains operation
Battery operation:	7-8 hours at max. volume
Battery type:	removable lead gel 12 V/4.5 Ah
Recharging time:	<45 hours
Output power:	15 W RMS/22 W max.
Components:	2-way system
Inputs:	1 x microphone (XLR/6.3 mm jack combination), 1 x instrument (6.3 mm jack),
	1 x AUX (stereo RCA)
Output:	1 x link (6.3 mm jack)
Audio player:	supports MP3 files
Available storage media:	USB devices and SD(HC) cards up to 32 GB
Files system:	FAT32
Number of files:	max. 999
Pitch adjustment:	±4 %, ±8 %, ±16 %
Display:	file name, elapsed time, remain time, bargraph, pitch adjustment in %
Dimensions (LxWxD):	275 x 350 x 445 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.